

CRANETAINER SYSTEM

www.cranetainersystem.com

425-415-6767

QUICK HOIST

US PAT NO 10155643 / US PAT NO 8353416



The Quick Hoist is designed to safely and quickly move unsecured loads and other loose materials around the jobsite with a crane.

It has a working load limit of 3000 lbs. and a load capacity of 4' x 4' x 4' high. The collapsible, light weight design has a tare weight of 150 lbs. It is easily operated by one or two workers and is compact for storage. The collapsible sides make it easy to load and unload materials and can be loaded by hand, forklift, or slings.



Flying pallets with slings can be hazardous because the pallet slats can break causing loads to shift and possibly spill. Also, materials are often not wrapped or secured safely to pallets and sometimes materials come non-palletized.

The Quick Hoist gives workers a safe option to move these materials.



FIBC sacks and one time lift bags can often have tears or holes in them which can cause a hazardous, non-compliant lift. These lifts can be placed into the Quick Hoist and then safely moved around the jobsite.



Sometimes homemade boxes and other contraptions are not load rated or certified for lifting. These can also be placed into the Quick Hoist and safely moved around the jobsite. The Quick Hoist is also handy to move workers tools and other equipment.



Materials can be offloaded from pallets directly into the Quick Hoist avoiding empty pallets strewn about the jobsite. These excess pallets add costs to labor, hauling and dump fees.